

THE MOWER WITH MORE MUSCLE FOR YOUR MONEY.

- **High Horsepower** A 23 horsepower engine from Kawasaki* to power through thick grass up to 3.1 acres per hour.
- Elite Cutting System Offered in three cutting widths (42", 48", and 54"), the Elite Deck easily cuts large volumes of grass and provides an attractive after-cut appearance.
- **7-Stage Deck Height** Allows you to quickly and easily adjust mowing height for different applications.
- **Hydro-Gear' ZT-2800 Transaxles** Proven and reliable transmissions with an external oil filter for easier maintenance and extended system life.
- Quick-Lift Lock Allows you to quickly raise the deck to avoid objects and locks the deck in travel height for transporting or storing.
- **Steel Fenders** Built with 14-gauge steel, the fenders protect the body and fuel tank from damage.
- Industry Leading Warranty Backed with a three year warranty with unlimited hours of residential use and industry leading lifetime warranties.



Steel Fenders - Protects fuel tank from sun and impact damage



Hydro-Gear ZT-2800 - Smooth operation and fully serviceable



42", 48", & 54" Elite Cutting System - Formed and welded 10-ga deck shell



Commercial Forks - Greaseable and lifetime warranty against breakage



Comfort Ride - Plush cushioned seat with armrests for extra comfort



*Unlimited hour limited residential warranty, see dealer for complete warranty details







	42" Deck	48" Deck	54" Deck
Model	2342KW	2348KW	2354KW
Engine			
Manufacturer		Kawasaki* FR	
Horsepower	23		
Displacement	726cc		
Air-cleaner	2 stage		
Cooling	Air-cooled Air-cooled		
Starter	Electric		
Engine warranty	3-Year		

Drive System	
Dual hydrostatic	Hydro-Gear® ZT-2800 transaxles (internal expansion tank)
Ground speed	7 mph
Parking brake	Integrated in transaxle
Towing capacity	100 lbs

Mower Deck			
Deck size	42"	48"	54"
Acres/hour*	2.4	2.7	3.1
Cutting height		1.5" - 4.5"	
Deck height adjustments		Manual lift, 1/2" increments	
Deck Quick-Lift	Integrated		
Deck engagement	Ogura" 87 ft-lbs		
Construction	10 ga formed & welded		
Blades	3 - 15.25" × 2.5"	3 - 17.25" × 2.5"	3 - 19.25" × 2.5"
Blade tip speed (approximate)	18,500 fpm		
Spindles	.75" effective diameter machined shaft		
Spindle housings	1pc keyless sealed cast aluminum		
Anti-scalp rollers	4		
Pulleys	Vented split 3/16" steel deep groove		

General				
Battery		12 Volt, 300cca		
Digital display		hour meter		
Fuel capacity		4 gallons		
Rear tires	20 x 8-10 GrassMaster	20 x 10-8 GrassMaster		
Front tires	13 x 6.5-6			
Frame	Welded 1" x 2", 2" x 2" tube, 10 ga formed			
Floor-pan	Removable, steel			
Seat		20" padded seat w/ armrests		

Dimensions				
Overall height	47"			
Overall width (with chute)	51.5" 57.5" 64"			
Overall length	76"			
Weight	730 lbs	750 lbs	763 lbs	





REDEFINING THE RESIDENTIAL MOWER.

- **High Horsepower** A 24 horsepower engine from Kawasaki* for proven power to tackle through thick grass up to 3.4 acres per hour.
- Full Clipping Control The OCDC comes standard to give you full control of your clippings. Keep grass out of the driveway, flower bed, and more.
- **Superior Comfort** A super plush seat with armrests to give the operator extra comfort for extended mowing periods.
- **Hydro-Gear' Drivetrain** ZT-3100 commercial-grade transaxles offer steel-cut gears, charge pumps, and shock valves for extended drivetrain performance.
- Large Drive Tires 22" rear drive tires provide more speed, stability, and traction when you need it.
- **Elite Cutting System** Offered in two cutting widths (48" and 54"), the Elite Deck easily cuts large volumes of grass with a manicured finish.
- Industry Leading Warranty Enjoy peace-of-mind with three years of warranty with unlimited hours of residential use and industry leading lifetime warranties.



Discharge Chute - Take full control of clippings with the OCDC



Hydro-Gear ZT-3100 - Commercial duty drivetrain with serviceable filters



Proven Power - 24hp Kawasaki engine for more performance and reliability



Large Rear Tires - More traction, more speed, and better stability



Comfort Ride - Custom plush cushion seat for superior comfort



*Unlimited hour limited residential warranty, see dealer for complete warranty details





	48" Deck	54" Deck	
Model	2448KW	2454KW	
Engine			
Manufacturer	Kawasaki* FR		
Horsepower	24		
Displacement	726cc		
Air-cleaner	2 stage		
Cooling	Air-cool	led	
Starter	Electric		
Engine warranty	3-Year	r	

Drive System	
Dual hydrostatic	Hydro-Gear® ZT-3100 transaxles
Ground speed	8 mph
Parking brake	Integrated in transaxle
Towing capacity	100 lbs

Mower Deck				
Deck size	48" 54"			
Acres/hour*	3.1	3.4		
Cutting height	1.5" -	4.5"		
Deck height adjustments	Manual lift, 1/2	2" increments		
Deck Quick-Lift	Integ	Integrated		
Deck engagement	Ogura* 87 ft-lbs			
Construction	10 ga formed & welded			
Blades	3 - 17.25" × 2.5"	3 - 19.25" x 2.5"		
Blade tip speed (approximate)	18,500 fpm			
Spindles	.75" effective diameter machined shaft			
Spindle housings	1pc keyless sealed cast aluminum			
Anti-scalp rollers	4			
Pulleys	Vented split 3/16" steel deep groove			

General		
Battery	12 Volt, 300cca	
Digital display	Hour meter	
Fuel capacity	4 gallons	
Rear tires	22 x 11-10	
Front tires	13 x 6.5-6	
Frame	Welded 1" x 2", 2" x 2" tube, 10 ga formed	
Floor-pan	Removable, steel	
Seat	Deluxe seat w/ armrests	

Dimensions			
Overall height	47"		
Overall width (chute down)	53" 59"		
Overall width (chute up)	57.25"	63.25"	
Overall length	76"		
Weight	775 lbs	788 lbs	



FILEULL



RESIDENTIAL

MODELS:

2448KW 24hp, 48" Deck 2454KW 24hp, 54" Deck 2460KW 24hp, 60" Deck



NOT YOUR TYPICAL RESIDENTIAL MOWER.

The Falcon HP is the newest residential mower from Dixie Chopper and packed with high-quality features, robust durability, and operator comfort and convenience for the most demanding homeowner.

- Proven Power Equipped with 24 horsepower Kawasaki® FR engines for years of trusted reliability and performance.
- Deep Deck The Falcon HP deck features a deep 10 gauge shell to tackle taller grass with ease.
- Commercial Drive System Hydro-Gear ZT-3100 transaxles offer steel-cut gears, charge pumps, and shock valves for extended drivetrain performance.
- Total Comfort The padded and over-sized bolstered seat hugs your torso for ultimate comfort.
- Peer' Turf Xtreme™ Spindles Maintenance free and constructed of high-strength ductile iron.
- Charge and Mow Keep your mobile device and accessories charged with a USB charging port.
- Ready to Accessorize The Falcon HP is ready to add a suite of accessories including Springer Forks, suspension seat, OCDC, mulch kit, light kit, striping kit, roll-over protection system, and more.



Kawasaki* Engines - Reliable power to tackle the toughest jobs



Hydro-Gear* ZT-3100 - Commercial duty drivetrain with serviceable filters



Deep Deck - Deep deck shell to tackle more volume



Falcon HP 2460KW shown

More Traction - Large 22" rear tires with semi-aggressive tread pattern



PEER* Spindles - Maintenance free with Contamination Exclusion Technology



*Unlimited hour limited warranty, see dealer for complete warranty details





	48" Deck	54" Deck	60" Deck
Model	2448KW	2454KW	2460KW
Engine			
Manufacturer	Kawasaki [®] FR		
Horsepower	24		
Displacement	726cc		
Air-cleaner	2 stage		
Cooling	Air-cooled		
Starter	Electric		

Drive System	
Dual hydrostatic	Hydro-Gear® ZT-3100
Ground speed	8 mph
Parking brake	Integrated in transaxle
Towing capacity	200 lbs

3-Year

Mower Deck			
Deck size	48"	54"	60"
Acres/hour*	3.1	3.4	3.8
Cutting height	1.5" - 5"		
OCDC (operator controlled discharge chute)	Optional accessory (hand-operated)		
Deck height adjustments	Manual lift, 1/2" increments		
Deck engagement	Warner* 150 ft-lbs		
Construction	10 ga formed & welded		
Blades	(3) -2.5" x 17" (3) - 2.5" x 19" (3) - 2.5" x 20.5"		(3) - 2.5" x 20.5"
Blade tip speed (approximate)	18,500 fpm		
Spindles	1.25" effective diameter machined shaft		
Spindle housings	Peer® Turf Xtreme™ ductile iron (sealed)		
Anti-scalp rollers	3		
Pulleys	7 ga steel deep groove Vented split 3/8"steel deep groove		

General		
Battery	12 Volt, 300cca	
Digital Display	hour meter, tachometer	
Fuel capacity	5 gallons	
Rear tires	22x11-10 - 350 Mag	
Front tires	13 x 6.5-6	
Frame	Welded 1" x 2", 2" x 2" tube, 11 ga formed	
Floor-pan	Removable, steel	
Seat	High-back adjustable padded seat w/ armrests	
Springer Forks	Optional accessory	

Dimensions			
Overall height (rollbar down)	51.5"		
Overall height (with optional rollbar up)		71.1"	
Overall width (chute down)	63.6"	69.6"	76"
Overall width (chute up)	49.2"	55.4"	61.9"
Overall length	74.1"		
Weight	820 lbs	830 lbs	840 lbs



Engine warranty

FILEUR F.P.



COMMERCIAL

MODELS:

2448KW 24hp, 48" Deck 2454KW 24hp, 54" Deck 2460KW 24hp, 60" Deck



COMMERCIAL CUTTER OR WEEKEND WARRIOR

The **Falcon HPX** is the new standard in entry-level commercial mowing with high-quality features, robust durability, and operator comfort and convenience.

- **Proven Power -** Equipped with 24 horsepower Kawasaki* FT engines for years of trusted reliability and performance.
- **Deep Deck** The Falcon HPX deck features a deep 10 gauge shell to tackle taller grass with ease.
- **Commercial Drive System** Hydro-Gear ZT-3100 transaxles offer steel-cut gears, charge pumps, and shock valves for extended drivetrain performance.
- **Total Comfort** The padded and over-sized bolstered seat hugs your torso for ultimate comfort.
- **Peer' Turf Xtreme™ Spindles** Maintenance free and constructed of high-strength ductile iron.
- **R.O.P.S.** Roll-over protection system comes standard to keep operators safe.
- Charge and Mow Keep your mobile device and accessories charged with a USB charging port.
- **Ready to Accessorize** The Falcon HPX is ready to add a suite of accessories including Springer Forks, suspension seat, OCDC, mulch kit, light kit, striping kit, and more.



Kawasaki Engines - Reliable power to tackle the toughest jobs



Hydro-Gear ZT-3100 - Commercial duty drivetrain with serviceable filters



Deep Deck - Deep deck shell to tackle more volume



Falcon HPX 2460KW shown

More Traction - Large 22" rear tires with semi-aggressive tread pattern



PEER' Spindles - Maintenance free with Contamination Exclusion Technology



*Unlimited hour limited warranty, see dealer for complete warranty details





	48" Deck	54" Deck	60" Deck
Model	2448KW	2454KW	2460KW
Engine			
Manufacturer	Kawasaki [®] FT		
Horsepower	24		
Displacement	726cc		
Air-cleaner	2 stage		
Cooling	Air-cooled		
Starter	Electric		
Engine warranty	3-Year		

Drive System	
Dual hydrostatic	Hydro-Gear® ZT-3100
Ground speed	8 mph
Parking brake	Integrated in transaxle
Towing capacity	200 lbs

Mower Deck			
Deck size	48"	54"	60"
Acres/hour*	3.1	3.4	3.8
Cutting height	1.5" - 5"		
OCDC (operator controlled discharge chute)	Optional accessory (hand-operated)		
Deck height adjustments	Manual lift, 1/2" increments		
Deck engagement	Warner* 150 ft-lbs		
Construction	10 ga formed & welded		
Blades	(3) -2.5" x 17"	(3) - 2.5" x 19"	(3) - 2.5" x 20.5"
Blade tip speed (approximate)	18,500 fpm		
Spindles	1.25" effective diameter machined shaft		
Spindle housings	Peer® Turf Xtreme™ ductile iron (sealed)		
Anti-scalp rollers	3		
Pulleys	7 ga steel deep groove Vented split 3/8"steel deep groove		

General		
Battery	12 Volt, 300cca	
Digital Display	hour meter, tachometer	
Fuel capacity	5 gallons	
Rear tires	22x11-10 - 350 Mag	
Front tires	13 x 6.5-6	
Frame	Welded 1" x 2", 2" x 2" tube, 11 ga formed	
Floor-pan	Removable, steel	
Seat	High-back adjustable padded seat w/ armrests	
Springer Forks	Optional accessory	

Dimensions			
Overall height (rollbar down)	51.5"		
Overall height (with optional rollbar up)		71.1"	
Overall width (chute down)	63.6"	69.6"	76"
Overall width (chute up)	49.2"	55.4"	61.9"
Overall length	74.1"		
Weight	870 lbs	880 lbs	890 lbs



COMMERCIAL MODELS: 2448KW 24hp, 48" Deck 2454KW 24hp, 54" Deck

DIXIE CHOPPER



2460KW 24hp, 60" Deck

The **BlackHawk** is built to redefine your mowing experience with superior value, advanced operator controls, commercial grade components, and unmatched performance.

- **Proven Power -** Equipped with 24 horsepower Kawasaki* engines for years of trusted reliability and performance.
- **Robust Deck** Offered in three cutting widths, the BlackHawk deck features a deep 7 gauge shell and **abrasion resistance baffles** to outlast the competition in extreme conditions.
- **Smoothest Steering** The Parker* transmissions offer super smooth steering up to 9 miles per hour in a compact, quiet, and efficient drivetrain.
- **Total Comfort** The padded and over-sized bolstered seat hugs your torso for ultimate comfort.
- Peer' Turf Xtreme™ Spindles Maintenance free and constructed of high-strength ductile iron.
- **R.O.P.S.** Roll-over protection system comes standard to keep operators safe.
- **Ready to Accessorize** The BlackHawk is ready to add a suite of accessories including Springer Forks, suspension seat, light kit, striping kit, and more.



Kawasaki Engines - Reliable power to tackle the toughest jobs



Parker* **HTE -** Smooth steering and 1,000 hour oil change intervals



48", 54", and 60" Decks - Deep 7 gauge shell to tackle deep grass



BlackHawk 2454KW shown

Hitch Receiver - Class 1 hitch for easier mounting of accessories



PEER* Spindles - Maintenance free with Contamination Exclusion Technology



*Unlimited hour limited warranty, see dealer for complete warranty details





	48" Deck	54" Deck	60" Deck
Model	2448KW	2454KW	2460KW
Engine			
Manufacturer	Kawasaki* FT		
Horsepower	24		
Displacement	726cc		
Air-cleaner	2 stage		
Cooling	Air-cooled		
Starter	Electric		
Engine warranty	3-Year		

Drive System	
Dual hydrostatic	Parker*HTE
Ground speed	9 mph
Parking brake	Integrated in transaxle
Towing capacity	200 lbs

Mower Deck				
Deck size	48"	54"	60"	
Acres/hour*	3.4	3.9	4.3	
Cutting height	1" - 5"			
OCDC (operator controlled discharge chute)	Optional accessory (foot-operated)			
Deck height adjustments	Manual lift, 1/4" increments			
Electric lift	Optional			
Deck engagement	Ogura" 150 ft-lbs			
Construction	7 ga formed & welded, Abrasion Resistance Baffles			
Blades	(3) -2.5" x 17" (3) - 2.5" x 19" (3) - 2.5" x 20.5"			
Blade tip speed (approximate)	18,500 fpm			
Spindles	1.25" effective diameter machined shaft			
Spindle housings	Peer® Turf Xtreme™ ductile iron (sealed)			
Anti-scalp rollers	4			
Pulleys	7 ga steel deep groove Vented split 3/8"steel deep groove			

General		
Battery	12 Volt, 350cca	
Digital Display	Tachometer, hour meter, fuel gauge	
Fuel capacity	7 gallons	
Rear tires	23 x 10.5-12 GrassMaster	
Front tires	13 × 6.5-6	
Frame	Welded C-channel, 7 ga formed	
Floor-pan	Removable, steel	
Seat	High-back adjustable padded seat w/ armrests	
Springer Forks	Optional accessory	

Dimensions					
Overall height (rollbar down)	50"				
Overall height (rollbar up)	71"				
Overall width (chute down)	63.6" 69.6" 76"				
Overall width (chute up)	49.2" 55.4" 61.9"				
Overall length (rollbar down)	85.8"				
Overall length (rollbar up)	81.3"				
Weight	1104 lbs 1114 lbs 1121 lbs				





WHERE COMMERCIAL **MEETS COMFORTABLE.**

The BlackHawk HP provides the superior mowing experience with advanced operator controls, commercial grade components, and best-in-class performance and comfort.

- Total Comfort Full suspension seat with padded design provides lateral stability and comfort.
- **Proven Power** Equipped with the industry preferred Kawasaki® FX engine for reliability and performance year after year.
- Smoothest Steering The Parker* transmissions offer super smooth steering up to 10 miles per hour in a compact, quiet, and efficient drivetrain.
- Robust Deck Offered in three cutting widths (48", 54", and 60"), the BlackHawk HP deck features a deep 7 gauge shell and abrasion resistance baffles to outlast the competition in extreme conditions.
- Peer* Turf Xtreme™ Spindles Maintenance free and constructed of high-strength ductile iron.
- Ready to Accessorize The BlackHawk HP is ready to add a suite of accessories including Springer Forks, electric deck lift, light kit, striping kit, and more.



Suspension Seat - Full suspension for ultimate comfort all day long



Parker' HTJ - Smooth steering and 1,000 hour oil change intervals



48", 54", 60" Decks - Deep 7 gauge shell to tackle tough grass with ease



Kawasaki* Engines - Reliable power to tackle the toughest jobs



PEER* Spindles - Maintenance free with Contamination Exclusion Technology



*Unlimited hour limited warranty, see dealer for complete warranty details





	48" Deck	54" Deck	60" Deck
Model	2448KW	2448KW 2454KW 2460I	
Engine			
Manufacturer	Kawasaki* FX		
Horsepower	23.5		
Displacement	726cc		
Air-cleaner	4 stage		
Cooling	Air-cooled		
Starter	Electric		
Engine warranty	3-Year		

Drive System			
Dual hydrostatic	Parker* HTJ		
Ground speed	10 mph		
Parking brake	Integrated in transaxle		
Towing capacity	200 lbs		

Mower Deck			
Deck size	48"	54"	60"
Acres/hour*	3.8	4.3	4.8
Cutting height		1" - 5"	
OCDC (operator controlled discharge chute)	Optional accessory (foot-operated)		
Deck height adjustments	Manual lift, 1/4" increments		
Electric lift	Optional		
Deck engagement	Ogura" 150 ft-lb		
Construction	7 ga forn	ned & welded, Abrasion Resistanc	e Baffles
Blades	(3) - 2.5" x 17"	(3) - 2.5" x 19"	(3) - 2.5" × 20.5"
Blade tip speed (approximate)		18,500 fpm	
Spindles	1.25" effective diameter machined shaft		
Spindle housings	Peer® Turf Xtreme™ ductile iron (sealed)		
Anti-scalp rollers	4		
Pulleys	7 ga vented split steel deep groove		

General	
Battery	12 Volt, 350cca
Digital Display	Tachometer, hour meter, fuel gauge
Fuel capacity	7 gallons
Rear tires	23 x 10.5-12 GrassMaster
Front tires	13 x 6.5-6
Frame	Welded C-channel, 7 ga formed
Floor-pan	Removable, steel
Seat	Full suspension, adjustable seat w/ armrests
Springer Forks	Optional accessory

Dimensions					
Overall height (rollbar down)	50"				
Overall height (rollbar up)	71"				
Overall width (chute down)	63.6" 69.6" 76"				
Overall width (chute up)	49.2" 55.4" 61.9"				
Overall length (rollbar down)	85.8"				
Overall length (rollbar up)	81.3"				
Weight	1124 lbs 1132 lbs 1140 lbs				





LADIES AND GENTLEMEN, THE EAGLE HAS LANDED.

The **Eagle** is loaded with commercial features and delivers more speed, power, and performance to maintain your home's property, commercial accounts, and everything in between.

- **Proven Power -** Equipped with the industry preferred 27 horsepower Kawasaki* FX engine for trusted reliability and performance.
- **Robust Deck** Offered in two cutting widths (54"and 60"), the Eagle's deck features a deep 7 gauge shell and **abrasion resistance baffles** to outlast the competition in extreme conditions.
- **Smooth AND Fast** The Parker* HTG series transmissions deliver a smooth drive up to 12 miles per hour in a reliable and efficient drivetrain.
- Enhanced Comfort Full suspension seat with a padded design and isolated platform provides ultimate comfort.
- Large Drive Tires 25" rear tires for more speed, stability, and operator comfort.
- Run-Flat Tires Flat front tires are a problem of the past with run-flat tires standard on the Eagle.



Ultimate Comfort - ISO mounted suspension seat for all-day comfort



Parker' HTG - Smooth steering and 1,000 hour oil change intervals



54" and 60" Decks - Deep 7 gauge shell to tackle deep grass with ease



Run-Flat Tires - Flat tires are a problem of the past



Turbinator* **Pre-Cleaner -** Exclusive feature removes debris for cleaner air



*Unlimited hour limited warranty, see dealer for complete warranty details





	54" Deck	60" Deck	
Model	2754KW	2760KW	
Engine			
Manufacturer	Kawas	aki [®] FX	
Horsepower	27		
Displacement	852cc		
Air-cleaner	4 stage & Turbinator® Pre-Cleaner		
Cooling	Air-cooled		
Starter	Electric		
Engine warranty	3-Year		

Drive System	
Dual hydrostatic	Parker®HTG (14cc)
Ground speed	12 mph
Parking brake	Integrated in transaxle
Towing capacity	1,000 lbs

Mower Deck			
Deck size	54"	60"	
Acres/hour	5.2	5.8	
Cutting height	1" -	- 5"	
OCDC (operator controlled discharge chute)	Optional accessory (foot-operated)		
Deck height adjustments	Manual lift, 1/4	4" increments	
Electric lift	Optional		
Deck engagement	Warner* 250 ft-lbs		
Construction	7 ga formed & welded, Ak	orasion Resistance Baffles	
Blades	(3) - 2.5" × 19" (3) - 2.5" × 20.5"		
Blade tip speed (approximate)	18,500 fpm		
Spindles	1.25" effective diameter machined shaft		
Spindle housings	Peer* Turf Xtreme™ ductile iron (sealed)		
Anti-scalp rollers	4		
Pulleys	7 ga steel deep groove	Vented split 3/8" steel deep groove	

General	
Battery	12 Volt, 350cca
Digital Display	Tachometer, hour meter, fuel gauge
Fuel capacity	8 gallons
Rear tires	25 x 12-12 GrassMaster
Front tires	15 x 6-8 (run-flat)
Frame	Welded C-channel, 7 ga formed
Floor-pan	Removable, steel
Seat	Full suspension, adjustable seat w/ armrests and isolated platform
Springer Forks	Optional

Dimensions				
Overall height (rollbar down)	52.7"			
Overall height (rollbar up)	77.7"			
Overall width (chute down)	70.3" 76.9"			
Overall width (chute up)	59.6" 66.1"			
Overall length (rollbar down)	88.5"			
Overall length (rollbar up)	84.6"			
Weight	1306 lbs	1322 lbs		





THE ULTIMATE MOWING EXPERIENCE.

The new **Eagle HP** provides the ultimate mowing experience with unmatched combination of speed, power, performance, and comfort.

- Fast Ground Speed Hydro-Gear® ZT-5400 gives operators speeds up to 14mph for faster ground transportation and increased productivity.
- **Pure Power -** Equipped with the industry preferred Kawasaki* FX engine or a 40hp Vanguard* Big Block EFI for more power and fuel savings.
- **Ultimate Comfort** Springer Forks come standard along with a high-back seat with padded armrests, recline, lumbar, and isolated platform.
- **Robust Deck** Offered in two cutting widths (60"and 72"), the Eagle HP deck features a deep 7 gauge shell and **abrasion resistance baffles** to outlast the competition in extreme conditions.
- **Wide Stance** Extra-wide frame offers enhanced operator comfort and improved stability when mowing hillsides.
- Run-Flat Tires Flat tires are a problem of the past with run-flat tires standard on the Eagle HP.



Hydro-Gear ZT-5400 - Speeds up to 14mph for increased productivity



Suspension Seat - High back, padded armrests, and isolated platform



60" and 72" Decks - Deep 7 gauge shell to tackle deep grass with ease



More Muscle - Engines up to 40hp and Turbinator* Pre-Cleaner



Springer Forks - Absorb bumps to provide smoother ride for operator



*Unlimited hour limited warranty, see dealer for complete warranty details





-	60"	60" Deck		72" Deck	
Model	3560KW	4060VGE	3572KW	4072VGE	
Engine					
Manufacturer	Kawasaki* FX	Vanguard® EFI	Kawasaki [®] FX	Vanguard® EFI	
Horsepower	35	40	35	40	
Displacement	999cc	993cc	999cc	993cc	
Air-cleaner		4 stage & Turbinator® Pre-Cleaner			
Cooling		Air-cooled			
Starter		Electric			
Engine warranty		3-Year			

Drive System			
Dual hydrostatic	Hydro-Gear® ZT-5400		
Ground speed	14 mph		
Parking brake	Integrated in transaxle		
Towing capacity	300 lbs (low-speed only)		

Mower Deck			
Deck size	60"	72"	
Acres/hour	6.7	8.1	
Cutting height	1" -	· 5"	
OCDC (operator controlled discharge chute)	Optional accessory (foot-operated)		
Deck height adjustments	Manual lift, 1/4" increments		
Electric lift	Optional		
Deck engagement	Warner* 250 ft-lbs		
Construction	7 ga formed & welded, Abrasion Resistance Baffles		
Blades	(3) - 2.5" × 20.5" (3) - 2.5" 24.5"		
Blade tip speed (approximate)	18,500 fpm		
Spindles	1.25" effective diameter machined shaft		
Spindle housings	Peer® Turf Xtreme™ ductile iron (sealed)		
Anti-scalp rollers	4		
Pulleys	Vented split 3/8" steel deep groove		

General			
Battery	12 Volt, 350cca		
Digital Display	Hour meter, fuel gauge		
Fuel capacity	10 gallons		
Rear tires	25 x 12-12 GrassMaster		
Front tires	15 x 6-8 (run-flat)		
Frame	Welded C-channel, 7 ga formed		
Floor-pan	Removable, steel		
Seat	High-back, full suspension, lumbar, recline, padded armrests, and isolated platform		
Springer Forks	Standard		

Dimensions				
Overall height (rollbar down)	55.25"			
Overall height (rollbar up)	78.5"			
Overall width (chute down)	77" 89.6"			.6"
Overall width (chute up)	67"		79.6"	
Overall length (rollbar down)	88.6" 90.9"		90.5"	92.8"
Overall length (rollbar up)	88.5"		90).4
Weight	1478 lbs	1466 lbs	1527 lbs	1515 lbs



CLASSIC

INDUSTRIAL

MODELS:

2760KW 27hp, 60" Deck 3560KW 35hp, 60" Deck 4060VGE 40hp, 60" Deck 3572KW 35hp, 72" Deck 4072VGE 40hp, 72" Deck



A TRUE CLASSIC AMERICAN WORKHORSE.

The **Classic** is the perfect definition of a workhorse mower with the combination of commercial quality and industrial features

- Power and More Power Powered by Kawasaki* FX or Vanguard* Big Block EFI engines up to 40 horsepower to power through tough jobs.
- **Lifetime Warranty Frame** The strongest frame in the industry with a 1"x 2" steel-tube chassis guaranteed not to break.
- **T-Gear Box** Eliminates side-load on pumps and backed with a 5-year or 3,000 hour warranty.
- Complete Discharge Control An operator controlled discharge chute (OCDC) allows you to switch from normal discharge to closing the chute on the fly, saving you time on clean-up.
- **Tried and True Decks** Offered in two productive deck widths (60" and 72") the Elite X Deck has been the staple piece to Dixie Chopper's reputation of cleanly cutting all types of grass.
- **Comfort Ride** Our suspension seat comes standard on every Classic model to provide a smooth ride in the roughest terrain.



Suspension Seat - Full suspension for ultimate comfort all day long



Pumps & Wheel Motors - Stronger transmissions for extended system life



60" and 72" Elite X Deck - Gives a quality cut in all types of grass



More Muscle - Engines up to 40hp and Turbinator* Pre-Cleaner



Spindle Package - Maintenance-free spindles and cooling fans come standard



*Unlimited hour limited warranty, see dealer for complete warranty details





		60" Deck		72"	Deck
Model	2760KW	3560KW	4060VGE	3572KW	4072VGE
Engine					
Manufacturer	Kawas	saki [®] FX	Vanguard® EFI	Kawasaki* FX	Vanguard® EFI
Horsepower	27	35	40	35	40
Displacement	852cc	999cc	993cc	999сс	993cc
Air-cleaner		4 stage & Turbinator® Pre-Cleaner			
Cooling		Air-cooled			
Starter		Electric			
Engine warranty		3-Year			

Drive System			
Pumps	Hydro-Gear* 16cc		
Wheel motors	Parker® DG280		
Ground speed	12 mph		
Parking brake	Automotive Style		
Towing capacity	2,000 lbs		

Mower Deck			
Deck size	60"	72"	
Acres/hour*	5.8	7	
Cutting height	1.25" - 5"		
OCDC (operator controlled discharge chute)	Standard		
Deck height adjustments	Manual lift, 1/4" increme	ents	
Electric lift	Optional		
Deck engagement	Ogura® 250 ft-lbs		
Construction	10 ga formed & welded	7 ga formed & welded	
Top plate	7 ga bolted (not welded)		
Blades	3 - 20.5" × 2.5" 3 - 24" × 2.5		
Blade tip speed (approximate)	18,000 fpm		
Spindles	1.25" effective diameter machined shaft		
Spindle housings	Peer® Turf Xtreme™ ductile iron (sealed)		
Spindle cooling fans	Standard (3)		
Anti-scalp rollers	4	5	
Pulleys	Vented split 3/16" steel deep groove		

General				
Battery	12 Volt, 350cca			
Digital display		Tachometer, hour meter, voltmeter, service alerts		
Fuel capacity	8 gallons	10 gallons	12 gallons	
Rear tires	25 x 12-12 GrassMaster			
Front tires	15 x 6-8 (run-flat)			
Frame	Welded 1" x 2" tube, 7 ga formed			
Floor-pan	Removable, steel			
Seat	Full suspension, adjustable seat w/ armrests			
Springer Forks		Optional		

Dimensions				
Overall height	53"			
Overall height (rollbar up)		78"		
Overall width	65.5" 76"			
Overall length	78.5"	80"		
Overall length (rollbar down)	81" 83"			
Weight	1134 lbs	1228 lbs	1425 lbs	





THE TOUGHEST MOWER IN THE ZERO-TURN INDUSTRY.

Professional commercial contractors and large property home owners have come to depend on the **XCaliber** for its legendary performance. Our flagship mower features:

- Pure Power Models powered with Kawasaki* FX or Vanguard® Big Block EFI engines up to 40 horsepower.
- X2 Wind Tunnel Deck The industry's best cutting deck available in 66" and 74" cutting widths for maximum productivity, "Wind Tunnel" front edge for increased discharge performance, and industry leading 2-inch blade overlap for precision cutting.
- **Ultimate Comfort** Springer Forks come standard along with a high-back seat with padded armrests, recline, and lumbar.
- **Productivity** Our heavy-duty pump and wheel motor drivetrain increases ground speed up to 13 mph to mow over 7 acres per hour.
- Wide Wheelbase An extra wide wheelbase assists in hillside performance and overall ride quality.
- Most Lifetime Warranties Worry-free lifetime warranties on the frame, front forks, steering levers, and front caster bearings.



Total Comfort - Suspension seat with recline, lumbar, and padded armrests



Pumps & Wheel Motors - Stronger transmissions for extended system life



Spindle Package - Maintenance-free spindles and cooling fans come standard



Springer Forks - Absorb bumps to provide smoother ride for operator



Wind Tunnel Deck - Increases airflow



*Unlimited hour limited warranty, see dealer for complete warranty details





	66" Deck		74"	Deck
Model	3566KW	4066VGE	3574KW	4074VGE
Engine				
Manufacturer	Kawasaki* FX	Vanguard* EFI	Kawasaki* FX	Vanguard® EFI
Horsepower	35	40	35	40
Displacement	999	993cc	999cc	993cc
Air-cleaner		4 stage & Turbinator® Pre-Cleaner		
Cooling		Air-cooled		
Starter		Electric		
Engine warranty		3-Year		

Drive System			
Pumps	Hydro-Gear* 21cc		
Wheel motors	Parker® DG335		
Ground speed	13 mph		
Parking brake	Automotive Style		
Towing capacity	2,000 lbs		

Mower Deck			
Deck size	66"	74"	
Acres/hour*	6.9	7.8	
Cutting height	1.25'	'' - 5"	
OCDC (operator controlled discharge chute)	Stan	ndard	
Deck height adjustments	Manual lift, 1/-	'4" increments	
Electric lift	Optional		
Deck engagement	Ogura® 250 ft-lbs		
Construction	7 ga formed & welded		
Top plate	7 ga bolted (not welded)		
Blades	3 - 23.3" × 2.5" 3 - 26" × 2.5"		
Blade tip speed (approximate)	18,000 fpm		
Spindle housings	Peer® Turf Xtreme™ ductile iron (sealed)		
Spindles	1.25" effective diameter machined shaft		
Anti-scalp rollers	6		
Spindle cooling fans	Standard (3)		
Pulleys	Vented split 3/16"	steel deep groove	

General	
Battery	12 Volt, 350cca
Digital display	Tachometer, hour meter, voltmeter, service alerts
Fuel capacity	12 gallons
Rear tires	25 x 12-12 GrassMaster
Front tires	15 x 6-8 15 x 6-8 (run-flat)
Frame	Welded 1" x 2" tube, 7 ga formed
Floor-pan	Removable, steel
Seat	High-back, full suspension, lumbar, recline, and padded armrests
Springer Forks	Standard

Dimensions		
Overall height	52"	53"
Overall height (rollbar up)	77.5"	
Overall width	72"	76"
Overall length	85"	86"
Overall length (rollbar down)	88.5"	89.5"
Weight	1445 lbs	1482 lbs





Talon M/S 700HPX shown

MEET THE HARDEST WORKER ON THE JOB SITE.

Dixie Chopper is now known for more than mowers. Meet the Talon M/S, a heavy-duty mini skid steer built for commercial contractors who do more than mowing. This new model is loaded with features, including:

- **Diesel Power** Reliability and efficient power comes standard with the 24.8 horsepower Kubota engine.
- **Gate Friendly** The 700HPX offers a hydraulically expandable undercarriage to retract the unit width less than 36" to fit in tight spaces.
- **Hydraulic Flow** Delivering up to 11.3 gpm to the auxiliary hydraulic flow, the Talon M/S attachments make easy work of tough jobs.
- All-Day Comfort The spring assisted stand-on platform design with generous hip padding provide operator comfort from start to finish.
- **Productivity** With the expandable undercarriage and speeds up to 4.5 mph, operators can safely and quickly get work done in record time.
- Compatibility Universal compact utility loader mounting plate and quick-attach system to easily switch between most standard attachments.

AVAILABLE ACCESSORIES

- Pallet Forks
- _ .
- Bucket
- Snow Blade
- Dozer Blade
- Auger
- Trencher
- Broom
- Grapple





Kubota Diesel - Quiet, powerful, and reliable diesel engine



Heavy Loads - Get more work done with 700+ pounds of operating capacity



Expandable Tracks - Narrow for tight spaces or wider for better stability



*Unlimited hour limited warranty, see dealer for complete warranty details





Model	700HPX
Engine	
Manufacturer	Kubota*
Horsepower	24.8
Fuel Type	Diesel
Fuel capacity	9 gallons
Cooling	Liquid
Starter	Electric
Engine warranty	2-Year

Hydraulic System	
Hydraulic capacity	24 gallons
System flow (total)	27.1 GPM
Hydraulic flow aux (high/low)	11.3 (high), 8.7 (low) GPM
Hydraulic flow (drive)	7.1 GPM
System pressure	3000 PSI
Tracks	
Track gauge	33.75"
Track width	9"
Ground speed	4.5 MPH
Ground Pressure	4.21 PSI

Dimensions	
Weight (no attachment)	2880 lbs
Length (no attachment)	77"
Length (with bucket)	96"
Width (fully retracted)	34.5"
Width (fully extended)	43.5"
Height (boom lowered)	54"
Height (boom raised)	98"
Hinge pin height	77"
Dump height	60"
Dump angle	37 degrees
Reach	34"
Tip capacity	2020 lbs
Operating capacity (35% of tip load)	707 lbs
Ground clearance	5"



CREATE RICE




REMOTE CONTROL



MOW WHERE NO MOWER HAS MOWED BEFORE.

The **Talon R/C** is the safest and most productive solution for commercial and municipal operators who need to maintain steep hills, ditches, wet terrains, and areas zero-turn mowers struggle to perform.

- Remote Control Keep operators safe in areas needing maintained with remote control technology with nearly 500 feet of range.
- American Muscle Powered by a 28 horsepower Vanguard® EFI engine, the Talon R/C has plenty of power to cut, climb, and maneuver any terrain.
- Hillside Ready Mow slopes up to 55 degrees in areas where operators should never be on the equipment.
- Hybrid Technology Electric drive system for advanced operator controls and variable speed.
- Low Ground Pressure Maximize your efficiency while minimizing your footprint.
- Variable Cutting Height Choose your cutting height on the remote from just one 1" all the way to 6" to get the perfect cut at every job.



Safe for Slopes - Safely mow slopes up to 55 degrees with ease



Hybrid Power - Electric drive system for smooth control



Bi-Directional Cutting - Improves efficiency by reducing turning



EFI Engine - Improved fuel economy and easier cold starts



Mulching Deck - Twin spindle design for attractive finish in all grass types.



*1 year or 1,500 hour limited warranty, see dealer for complete details







	44" Deck
Model	2844VGE
Engine	
Manufacturer	Vanguard® EFI and Oil Guard System
Horsepower	28
Displacement	810cc
Air-cleaner	4 stage & Turbinator® Pre-Cleaner
Cooling	Air-cooled Air-cooled
Starter	Electric
Fuel capacity	2 gallons
Maximum noise levels	98 db(A)
Engine warranty	3-Year

Drive System	
Drive motors	48V AC electric motor to final reduction
Ground speed	5 mph

Mower Deck	
Deck size	44"
Discharge	Rear
Cutting height	1" - 6"
Programmable low height setting	Standard
Bi-directional cutting	Standard
High Lift mulching blades	Standard
Deck Engagement	Ogura" 250 ft-lbs
Blade tip speed (approximate)	18,044 fpm
Fast-stop rotors	Standard (3 seconds)

Tracks	
Universal rubber	Standard
Maximum working angle	55 degrees in side to side mowing applications
Track length	39.4"

Remote Controls	
Working range	492 feet
Frequency	434 Mhz
Battery	2 rechargeable batteries
Proportional joysticks	Standard

Dimensions	
Overall height (deck at lowest height)	30.1"
Overall height (deck at highest height)	36"
Overall width	59"
Overall length (without attachment)	59.5"
Weight	1058 lbs

